

One of the world's leading
manufacturers of automated
cleaning & handling equipment

NEWSMITH

www.newsmiths.co.uk



Trayline Series

**Continuous wash and rinse machine for
boxes, crates and baskets**

- Machine body constructed entirely from stainless steel
- Machine designed for economical running costs, easy operation and maintenance
- Access doors both sides with operator protection
- Optional one person operation attachment

Tel: +44 (0) 1924 405988

One of the world's leading manufacturers of automated cleaning & handling equipment



NEWSMITH

www.newsmiths.co.uk

Standard Features

- Stainless steel conveyor system
- Large tank capacity minimises water changes
- Machines have built-in immersion heater protection
- Wash and rinse from spray arms cleans all round
- Easy access to wash pipes and filters



TRAYLINE

2
Length 3100mm (plus 200mm with OPO attachment)
Width 940mm (overall)
Height 1590mm (plus 390mm with OPO attachment)
Wash Design 200 trays per hour (600mm x 400mm)
Wash Pump 4kW (5½hp)
Drive Motor 0.18kW (¼hp) Fixed Speed
Wash Tank 300 Litre (66 gallons)
Fresh Rinse Usage 4.5 Litres per min @ 1.5 bar
Conveyor Width 475mm (max. tray width 450mm)
Feed Opening 300mm (max tray height 250mm with OPO attachment)
Wash Heating 30kW standard (20kW economy version)
 *Other forms of heating available.
Wash Tank Filler ¾" bsp
Drain 2" bsp
Overflow 1¼" bsp
Hot Rinse Supply ¾" bsp (1.5 bar min)
 34.18kW standard (24.18kW economy version) plus
 rinse (20kW) if rinse heater fitted. Supply 400v 3ph
 50hz.

3
Length 3660mm (plus 200mm with OPO attachment)
Width 1050mm (overall)
Height 1590mm (plus 390mm with OPO attachment)
Wash Design 300 trays per hour (762mm x 457mm)
Wash Pump 5.5kW (7½hp)
Drive Motor 0.18kW (¼hp) Variable Speed
Wash Tank 450 Litre (100 gallons)
Fresh Rinse Usage 5.5 Litres per min @ 1.5 bar
Conveyor Width 584mm (max. tray width 559mm)
Feed Opening 300mm (max tray height 250mm with OPO attachment)
Wash Heating 40kW standard
 *Other forms of heating available.
Wash Tank Filler ¾" bsp
Drain 2" bsp
Overflow 1¼" bsp
Hot Rinse Supply ¾" bsp (1.5 bar min)
 45.78kW standard (24.18kW economy version) plus
 rinse (20kW) if rinse heater fitted. Supply 400v 3ph
 50hz.

78i1g8"i7W8"O hSWL785 hrhi1Sh Oi0

n)s)1s)))tse)1fi)

e)#e))t se))89LF8)

fi)t 5)9) 3882V@85@CP)))3PS2)S@P508

g V) d 6)
6 6

